



- NOTES:
1. CONCRETE: 5,000 PSI MIN. AFTER 28 DAYS
  2. ALL REINFORCEMENT PER ASTM C1227-93
  3. TEES AND GAS BAFFLE SOLD SEPARATELY
  4. TONGUE & GROOVE JOINT SEALED WITH BUTYL RESIN
  5. 4" POLYLOK IV CLOSED END BOOTS USED FOR CONNECTIONS.
  6. PLASTIC RISERS CAN BE POURED INTO COVER
  7. PUMPS & ACCESSORIES OPTIONAL

4" THICK WALLS  
 4" POLYLOK CLOSED END BOOT (TYP.)

24" DIA. ACCESS COVERS (TYP.)

**1,600 MONO H-20  
 2 COMPARTMENT TANK**



100 COACHECO RD.  
 FARMINGTON, NH 03835  
 OFFICE: (603) 755-2515  
 FAX: (603) 278-7878

<b>1,600 MONO TANK H-20 2 COMPARTMENT</b>	
FOR: AJ FOSS	DATE: Feb. 11, 2016
100 COACHECO ROAD	FILE NAME: 1600 MONO-H-20 2 COMPARTMENT
FARMINGTON NH 03835	DRAWN BY: SO
PHONE: (603) 755-2515	
FAX: (603) 278-7878	