



- NOTES:
1. CONCRETE: 5,000PSI MIN AFTER 28 DAYS.
  2. ALL REINFORCEMENT PER ASTM C1227-93.
  3. TEES AND GAS BAFFLE SOLD SEPARATELY.
  4. TONGUE & GROOVE JOINT SEALED WITH BUTYLE RESIN.
  5. 4" POLYLOK IV CLOSED END BOOTS USED FOR CONNECTIONS.
  6. PLASTIC RISER CAN BE POURED INTO COVER.
  7. PUMPS & ACCESSORIES OPTIONAL

	PREPARED FOR: <b>ANDREW J. FOSS CO. INC.</b> 100 COCHECO ROAD FARMINGTON, NH 03835 PHONE(603)755-2515 FAX(603)278-7878		
	REV.NO. DATE REVISION		PREPARED BY: 184 COURT STREET, BINGHAMTON, NY 13901 TEL: (607) 231-6600 FAX: (607) 231-6650
	DATE: 9/16/09 SCALE: N.T.S.	SHEET TITLE: SKETCH PROJECT: 2184 GALLON TANK 384 GALLON CHAMBER H-20	DRWN BY: GJP CKD BY: KMK CONTRACTOR: DELTA PROJ. NO.: 2009.367.001
			DWG. I.D. SK-01 SHT. NO. 1 OF 1