


- NOTES:
1. CONCRETE: 5,000 PSI MIN AFTER 28 DAYS.
  2. TYPE III CEMENT.
  3. TEST BAFFLES SOLD SEPARATELY.
  4. 4" POLYLOK IV CLOSED END BOOTS USED FOR CONNECTIONS.
  5. JOINT SEALED WITH BUTYLE RESIN.
  6. PUMPS & ACCESSORIES OPTIONAL
  7. PLASTIC RISER CAN BE POURED INTO COVER.

PREPARED FOR: <b>ANDREW J. FOSS CO. INC.</b> 100 COCHECO ROAD FARMINGTON, NH 03835 PHONE(603)755-2515 FAX(603)278-7878		
DATE: 9/18/09 SCALE: N.T.S.	SHEET TITLE: SKETCH	DRWN BY: GJP CKD BY:
PROJECT: 4' x 4'-6" PUMP BOX		
CONTRACTOR: DELTA PROJ. NO.: 2009.367.001		DWG. I.D. SK-01 SHT. NO. 1 OF 1

REV. NO.	DATE	REVISION

PREPARED BY:  
  
**DELTA**  
 ENGINEERS, ARCHITECTS, & LAND SURVEYORS  
 184 COURT STREET, BINGHAMTON, NY 13901  
 TEL: (607) 231-6600 FAX: (607) 231-6650